NEC
LH17m

- LCD 17" Monitor (TN + TFT Film)
- Height adjustment
- Swivel and Portrait/Landscape switch
- Integrated speakers

NEC LH17m

Screen

Size	17 inches
Type	Active colour matrix
	TFT
Visability angle	Horizontal +/- 80°
	Vertical +/- 80°
Inch per pixel	0,264 mm
Display zone	337.9mm x 270.3mm
Resolution	1024 x 768 x 75 Hz
Number of colours	16. 2 million
Contrast ratio	500:1
Response time	8ms
Luminance	300 cd/m2
Backlight	4 CCFL (Cold Cathode light)

Scanning frequency

Horizontal	30 kHz - 80 kHz
Vertical	60 kHz - 75 kHz

Control option

On Front	Power SW, exit Control (left/right), Adjustment (left/right), select, reset
OSD	Luminance, contrast, Auto Cont Auto adjustment, Position H, Position V, Size H, control colour, Language, position OSD, extinction OSD, lock OSD, Hot key, Resolution adjustment, Timer, Reset, Screen mode, Information
Order	VESA DDC2B

Other resolutions

800 x 600 @ 56Hz/60Hz/72Hz/75Hz
1024 x 768 @ 60Hz/70Hz/75Hz

Power

Voltage	AC 100-240V
On	< 48W
Stand by	<3W

Audio system

Speakers	1W + 1W

Entry signal

Video	Analogical RGB
Connectors	Mini D-sub 15 pins
Cable	1,80m

Ergonomics, Security, Certification

Ergonomics	**Height adjustment** (130 mm) **Swivel** (+/- 40°) **Portrait/Landscape switch**
Security	UL 1950 (UL), CSA C22.2 No.950 (C-UL) CE Marketing, TUV-GS (EN60950) **Kensington Lock**
EMC	FCC-B, DOC-B, EN55022-B, EN61000-3-2,-3-3 EN55024 (IEC6100-4-2,-4-3,-4-4,-4-5, -4-6,-4-8,-4,11)
VLF/ELF	MPR-II, TCO 03
Power	EPA, TCO 03
Ergonomy	MPR-II, TCO 03, ISO 13406-2, Energy Star
Plug and Play	DPMS, VESA DDC 1/2B

Conditions of use

Temperature	5-40°C
Humidity	20-85% (without condensation)
Altitude	0-3,000m

Dimensions (W x H x D)

Screen	377 x 380/510 x 200 mm
Weight	11,46 lb
Packaging Inc	435 x 455 x 250 mm
Weight (packaging Inc)	15,4 lb